

doseBadge Industrial Noise Dosimeter



(c) NoiseMeters

Features

- Strong metal case
- Shoulder mounted
- Measures noise exposure
- No cables, controls or display

Applications

- Noise at work assessments
- Occupational noise surveys
- Factory noise
- Noise dosimetry
- Hearing protection

Overview

The doseBadge noise dosimeter mounts on a worker's shoulder to measure and store the noise exposure throughout the working day or shift. The doseBadge contains a rechargeable battery, microphone and acoustic processor, all inside a strong metal case that clips on to the worker's clothing or overalls. It is well positioned to measure the noise levels close to the ear.

The doseBadges are controlled using a Reader (included in the CK110/x kits). The Reader communicates with the doseBadge over an infrared link, like a TV remote control. This means you can mount the doseBadge on the worker and, once you have finished fitting it, start the actual measurement.

The Reader also includes a sound level calibrator to check the function of each doseBadge before use. This is a requirement of most occupational noise regulations.

Noise in the Workplace



The doseBadge is designed to measure occupational noise exposure in areas with high sound levels (above 70 dB) to determine whether the noise levels need to be reduced or hearing protection provided.

It has programmable settings to satisfy the occupational noise regulations from around the world, such as those for US OSHA and the European and UK noise at work regulations.

doseBadge Industrial Noise Dosimeter

Specifications

Standards	ANSI S1.25:1991 Personal Noise Dosimeters Class Designation 2AS-90/80-5 IEC 61252:1993 Personal Sound Exposure Meters Reader's Acoustic Calibrator to IEC 60942:2003 Class 2	Memory	CR:110A doseBadge: up to 24 hours of data in a single measurement RC:110A Reader: up to 999 individual doseBadge measurements
Range	70 dB(A) to 130 dB(A) RMS 120 dB(C) to 140 dB(C) Peak	Power	doseBadge: NiMH rechargeable battery Reader: 2 x AA/LR6 with auto power switch off
Stored Functions	All configurations: doseBadge Settings, Calibration Record Measurement Duration, Highest Peak (C) Sound Level Overload Exceedance, Battery Status 115 dB(A) Maximum Sound Level Exceedance 1 Minute Time History of: LAeq (3dB), Lavg (4dB or 5dB), Peak (C) Level, Battery Level For 3dB Exchange Rate: LAeq, LEX,8h, LAE, % Dose, Exposure (Pa2h) Estimated % Dose, Estimated Exposure (Pa2h) For 4dB & 5dB Exchange Rates: Lavg, TWA, % Dose Estimated % Dose "A" for all RMS measurements. "C" for Peak Sound Pressure	Outputs	CU:195A Mains Power Supply with UK, EU or US plug doseBadge: Infrared to RC:110A Reader Unit Reader: USB 2.0 to computer
Weightings		Dimensions	Microphone Apex Ø13.0mm, Base Ø47mm, Height 38mm
Configuration	ISO (Q=3, Time=None) OSHA (Q=5, Time=Slow) User programmable: Exchange Rate (3dB, 4dB or 5dB) Criterion Level (80dB, 85dB, 87dB, 90dB) Criterion Time (8hrs, 12hrs, 16hrs, 18hrs) Threshold (None, 80dB, 85dB, 90dB) Time Weighting (None, Slow)	Weight	doseBadge: 45gms (1.6oz) Reader: 400gms (14oz)
		Temperature	-10 °C to +50 °C Operating -20 °C to +60 °C Storage
		Humidity	Up to 95%RH Non-Condensing
		General Features	
		<ul style="list-style-type: none"> ● No wires or controls on the badge to catch or knock ● Channel 1: programmable exchange rate, time weighting, criterion time and level ● E.g. Q=3 (ISO) or Q=5 (OSHA), etc. ● Extra user-programmable settings for MSHA, AICHE and ACGIH noise regulations ● Channel 2: Q=3dB (ISO): Leq, Dose %, Lep,d and Peak ● "A" frequency weighting with "C" weighting for Peak ● Powered by an internal rechargeable battery ● doseBadge and Reader communicate using an infra-red link ● Time history gives graph of noise levels ● True Peak reading with Peak Time history ● 115 dB(A) sound level exceeded flag 	

Head Office

NoiseMeters Ltd
7 Jayes Park
Ockley
Surrey
RH5 5RR

Telephone **+44 130 677 0855**
Fax **+44 845 680 0316**

Email: **info@noisemeters.com**
Support: **support@noisemeters.com**

Web Sites

Main site:
<https://eu.noisemeters.com>

Product shortcut:
<https://eu.noisemeters.com/p/ck110/1/>

Tech Support:
<https://support.noisemeters.com>